

Our Ref: GBW Number 94997-1 Issue 1 Date 16/04/2012 Page 1 of 1

A/C No: M114

Tested For:-

T I MIDWOOD & COMPANY LIMITED
Green Lane
Wardle
Nantwich
Cheshire
CW5 6BJ

SALT SPRAY TESTING OF TIMCO DECKING SCREW SAMPLES

INTRODUCTION

The finished samples were submitted to the laboratory for Salt Spray Corrosion Resistance Testing in accordance with the relevant specification.

RELEVANT INFORMATION

Description: 12 off. Timco Green Decking Screw Samples
Finish: Green Powder Coating
Specification: Salt Spray Test in accordance with ASTM.B117-09
Test Duration: 1008 Hours Exposure
Submitted By: Peter Owen
Customer's Order No: Verbal
Sample Receipt Date: 27/02/2012

RESULTS

Salt Spray Test (ASTM B117-09 / BS EN ISO 9227:2006 / DIN.50.021-SS)

The screw samples were exposed to a neutral 5% Salt Spray for a test period of 1008 hours.

The screw heads of the samples showed no evidence of red ferrous corrosion on the heads of the screws after 1008 hours exposure.

CONCLUSION

The finish applied to the Timco Green Decking Screw Samples tested, **satisfied** 1008 hours Salt Spray Test without the formation of red ferrous corrosion.

REPORT COMPILED BY



G B Withers
Corrosion Science
Technician

REPORT APPROVED BY



G B Withers
Corrosion Science
Technician

TESTS MARKED "NOT UKAS ACCREDITED" IN THIS REPORT/CERTIFICATE ARE NOT INCLUDED IN THE UKAS ACCREDITATION SCHEDULE FOR OUR LABORATORY.
TESTS MARKED 'SC' HAVE BEEN SUBCONTRACTED.
OPINIONS AND INTERPRETATIONS EXPRESSED HEREIN ARE OUTSIDE THE SCOPE OF UKAS ACCREDITATION.
THIS TEST REPORT SHALL NOT BE REPRODUCED EXCEPT IN FULL, WITHOUT WRITTEN APPROVAL OF THE LABORATORY.
RESULTS IN THIS REPORT RELATE ONLY TO THE ITEMS TESTED.